



INTERNATIONAL TELECOMMUNICATION UNION

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**Q.772**

(06/97)

SERIES Q: SWITCHING AND SIGNALLING

Specifications of Signalling System No. 7 – Transaction  
capabilities application part

---

**Transaction capabilities information element  
definitions**

ITU-T Recommendation Q.772

(Previously CCITT Recommendation)

---

ITU-T Q-SERIES RECOMMENDATIONS  
**SWITCHING AND SIGNALLING**

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4 AND No. 5	Q.120–Q.249
SPECIFICATIONS OF SIGNALLING SYSTEM No. 6	Q.250–Q.309
SPECIFICATIONS OF SIGNALLING SYSTEM R1	Q.310–Q.399
SPECIFICATIONS OF SIGNALLING SYSTEM R2	Q.400–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.849
General	Q.700
Message transfer part (MTP)	Q.701–Q.709
Signalling connection control part (SCCP)	Q.711–Q.719
Telephone user part (TUP)	Q.720–Q.729
ISDN supplementary services	Q.730–Q.739
Data user part	Q.740–Q.749
Signalling System No. 7 management	Q.750–Q.759
ISDN user part	Q.760–Q.769
<b>Transaction capabilities application part</b>	<b>Q.770–Q.779</b>
Test specification	Q.780–Q.799
Q3 interface	Q.800–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
General	Q.850–Q.919
Data link layer	Q.920–Q.929
Network layer	Q.930–Q.939
User-network management	Q.940–Q.949
Stage 3 description for supplementary services using DSS 1	Q.950–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1999
BROADBAND ISDN	Q.2000–Q.2999

*For further details, please refer to ITU-T List of Recommendations.*

## **ITU-T RECOMMENDATION Q.772**

### **TRANSACTION CAPABILITIES INFORMATION ELEMENT DEFINITIONS**

#### **Summary**

This Recommendation describes individual information elements and parameters used within transaction capabilities messages. It has been revised for the definition of result source diagnostic.

#### **Source**

ITU-T Recommendation Q.772 was revised by ITU-T Study Group 11 (1997-2000) and was approved under the WTSC Resolution No. 1 procedure on the 5th of June 1997.

## FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

## INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had/had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 1998

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

## CONTENTS

	<b>Page</b>
1 General .....	1
2 Transaction portion.....	1
2.1 Message type .....	1
2.2 Transaction IDs .....	1
3 Component Portion .....	3
3.1 Component type .....	3
4 Dialogue portion.....	7
4.1 Dialogue control APDUs.....	7
4.2 Dialogue portion information elements.....	7



## Recommendation Q.772

### TRANSACTION CAPABILITIES INFORMATION ELEMENT DEFINITIONS

*(Melbourne 1988; revised in 1993 and 1997)*

#### 1 General

This Recommendation describes the individual information elements and parameters used within Transaction Capabilities messages. The encoding and formatting of these elements are shown in Recommendation Q.773.

The meaning of each information element is described in general terms.

The TCAP message format consists of three parts, namely the transaction portion, the dialogue portion and the component portion. Information in the component portion concerns individual operations and their replies. The transaction portion contains protocol control information for the transaction sublayer. The dialogue portion is concerned with the application context and, as an option, user information (i.e. data, which are not components).

For a more detailed analysis of the architecture, see Figure 1/Q.771 and associated text.

#### 2 Transaction portion

The transaction portion of a TC message may contain the following information elements, namely:

##### 2.1 Message type

Five types of messages are defined for the transaction portion as follows:

**2.1.1 unidirectional:** This message is used when there is no need to establish a transaction with another peer TR-User.

**2.1.2 begin:** This message is used to initiate a transaction with another peer TR-User.

**2.1.3 end:** This message is used to terminate a transaction with another peer TR-User.

**2.1.4 continue:** This message is used to complete the establishment of a transaction and to continue an established transaction.

**2.1.5 abort:** This message is used to terminate a transaction following an abnormal situation detected by the transaction sublayer (the service provider), or to abort a transaction by the TR-User (the service user).

##### 2.2 Transaction IDs

Transaction IDs are independently assigned by each of the two nodes communicating via a transaction, enabling each node to uniquely identify the transaction and associate the entire contents of the message with that particular transaction. There are two types of Transaction IDs, namely:

**2.2.1 originating transaction ID:** The Originating Transaction ID is assigned by the node sending a message, and is used to identify the transaction at that end.

**2.2.2 destination transaction ID:** The Destination Transaction ID identifies the transaction at the receiving end.

**2.3 P-abort cause:** This is used when the transaction sublayer aborts a transaction.

P-Abort cause definitions are as follows:

**2.3.1 unrecognized message type:** The message type is not one of those defined in 2.1.1 to 2.1.5 above.

**2.3.2 unrecognized transaction ID:** A transaction ID has been received for which a transaction does not exist at the receiving node.

**2.3.3 badly formatted transaction portion:** The transaction portion of the received message does not conform to the X.209 encoding rules as outlined in 4.1/Q.773.

**2.3.4 incorrect transaction portion:** The elemental structure within the transaction portion of the received message does not conform to the rules for the transaction portion defined in 3.1/Q.773.

**2.3.5 resource limitation:** Sufficient resources are not available to start a transaction.

**Table 1/Q.772 – Example mapping of P-Abort scenarios to P-Abort cause values**

<b>Transaction sublayer</b>	
<b>P-Abort cause</b>	<b>Example reason</b>
Unrecognized message type (syntax error)  (The message type tag is unknown, i.e. not defined in Recommendation Q.773)	The combination of class, form and value does not correspond to a known tag, i.e. message type is not Begin, Continue, End, Uni-directional or Abort.
Unrecognized transaction ID  [A Transaction ID has been received which is derivable, but for which a transaction does not exist at the receiving node, i.e. a Continue message has been received with an unrecognized (destination) Transaction ID]	Destination Transaction ID unassigned.
Badly formatted transaction portion (encoding error)  (The Transaction Sublayer has received a message which does not conform to the encoding rules defined in 4.1/Q.773)	Length indicator value has less than 128 octets, but not coded short form.
	Malformed tag for an information element, other than Message Type (e.g. the class and code indicates integer while the form indicates constructed encoding).
	Length indicator value does not correspond to length of message.

**Table 1/Q.772 – Example mapping of P-Abort scenarios to P-Abort cause values (concluded)**

<b>Transaction sublayer</b>	
<b>P-Abort cause</b>	<b>Example reason</b>
Incorrect transaction portion (syntax error)  (The elemental structure within the Transaction portion of the received message does not conform to the rules for the Transaction Portion defined in clause 3/Q.773)	Combination of Origin and Destination Transactions ID does not conform to message type.
	Component Portion Tag present, but no components.
	Message does not contain all the mandatory information elements defined in Recommendation Q.773 for the message type.
	The order of the received information elements within the message does not conform to Recommendation Q.773 for the message type.
Resource limitation  (Insufficient resources for this TR and/or TR-User)	Congestion
	No Transaction ID is available for allocation to the new transaction establishment request.

**2.4 dialogue portion:** This is used to pass Information related to application context and, as an option, user information (i.e. data, which are not components).

**2.5 component portion:** This contains components. When no components are transferred, this information element is not present.

### 3 Component Portion

The Component Portion contains the following types of information elements. Components within a message are delivered to the user at the receiving end in the same order in which they were received from the user at the originating end.

#### 3.1 Component type

There are five types of components that may be present in the Component Portion of a TC message. The four Protocol Data Units (PDUs) defined in Recommendation X.229 are used, namely:

<b>TCAP component</b>	<b>X.229 PDU</b>
Invoke	ROIV
Return result (last)	RORS
Return error	ROER
Reject	RORJ

The remaining component type – Return Result (Not Last) – is defined by TCAP.

These component types are defined as follows:

**3.1.1 invoke:** The invoke component requests that an operation be performed. It may be linked to another operation invocation previously sent by the other end. In this case it is known as a "Linked Invoke".

**3.1.2 return result (not last):** When TC uses a connectionless Network Service, it may be necessary for the TC-User to segment the result of an operation if the two peer TC-users use a network service that does not provide segmenting/reassembling of user data. In this case the Return Result (Not Last) component is used to convey each segment of the result except the last, which is conveyed in a Return Result (Last) component.

The Return Result (Not Last) facility is allowed ONLY if the result is too large to fit into a single Return Result (Last) component. Note that the use of the Return Result (Not Last) facility implies that the operation has completed successfully.

**3.1.3 return result (last):** The Return Result (Last) component reports successful completion of an operation. It may contain the last segment of a result or, in the case of an unsegmented result, it contains the entire result.

**3.1.4 return error:** The Return Error component reports that an operation has not been successfully completed.

**3.1.5 reject:** The Reject component reports the receipt and rejection of an incorrect component, other than a Reject component. The possible causes for rejecting a component are defined by the Problem Code element in 3.7.

**3.2 invoke ID:** An Invoke ID is used as a reference number to identify uniquely an operation invocation. It is present in the Invoke component and in any reply to the Invoke (Return Result, Return Error or Reject), enabling the reply to be correlated with the invoke.

**3.3 linked ID:** A Linked ID is included in an invoke component by a node when it responds to an operation invocation with a linked operation invocation. The node receiving the Linked ID uses it for correlation purposes, in the same way that it uses the invoke ID in Return Result, Return Error and Reject components.

**3.4 operation code:** The Operation Code element indicates the precise operation to be invoked, and is present in an Invoke component type. It is also present in the Return Result (Last/Not Last) components if the results contain parameters.

The operation code may be given a local value (i.e. integer) which then identifies the operation within a limited domain; or it may be a global value (i.e. object identifier) which makes the operation uniquely identifiable across all applications.

The actual operation codes, the definition of the operations and their associated parameters, are defined in relevant ASE specifications. The component sublayer does not set or examine the operation code value, nor parameters which are present, nor the parameter values.

**3.5 parameter:** The Parameter element contains one or several user information elements accompanying a component. The information elements themselves are defined in relevant ASE specifications.

**3.6 error code:** The Error Code element contains the reason why an operation cannot be completed successfully. It is present only in a Return Error component. As with operations, errors may be local or global. These errors and associated parameters are defined in relevant ASE specifications.

**3.7 problem code:** The Problem code element contains the reason for the rejection of a component, and one such element is present in a Reject component. Four problem code elements are defined, namely:

**3.7.1 general problem:** This element contains one of the problem codes which apply to the component sublayer in general, and which do not relate to any specific component type. All of these are generated by the component sublayer. They are:

**3.7.1.1 unrecognized component:** The component type is not recognized as being one of those defined in 3.1.

**3.7.1.2 mistyped component:** The elemental structure of a component does not conform to the structure of that component as defined in 3.1/Q.773.

**3.7.1.3 badly structured component:** The contents of the component do not conform to the encoding rules defined in 4.1/Q.773.

**3.7.2 invoke problem:** This element contains one of the problem codes that relate only to the invoke component type. They are:

**3.7.2.1 duplicate invoke ID:** The invoke ID is that of a previously invoked operation which has not been completed. This code is generated by the TC-User.

**3.7.2.2 unrecognized operation:** The operation code is not one of those agreed by the two TC-User.

**3.7.2.3 mistyped parameter:** Signifies that the type of parameter in an invoke component is not that agreed by the two TC-Users.

**3.7.2.4 resource limitation:** Sufficient resources are not available to perform the requested operation. This code is generated by the TC-User.

**3.7.2.5 initiating release:** The requested operation cannot be invoked because the dialogue is about to be released. This code is generated only by the TC-User.

**3.7.2.6 unrecognized linked ID:** The linked ID does not correspond to an active invoke operation. This code is generated only by the component sublayer.

**3.7.2.7 linked response unexpected:** The operation referred to by the linked ID is not an operation for which linked invokes are allowed. This code is generated only by the TC-User.

**Table 2/Q.772 – Example mapping of general problem reject scenarios to general problem reject types**

<b>Component sublayer</b>	
<b>General problem</b>	<b>Example reason</b>
Unrecognized Component (The component type is not recognized as being one of those defined in 3.1)	Component Type Tag not recognized as Invoke, Return Result Not Last, Return Error, Reject or Return Result Last.
Mistyped Component (The elemental structure of a component does not conform to the structure of that component as defined in 3.1/Q.773)	Missing Invoke ID element.
	Operation code element expected but not present.
	Return Error Component received with no Error Code Element.
Badly structured Component (The contents of the component do not conform to the encoding rules defined in 4.1/Q.773)	The order of the received information elements within the component does not conform to Recommendation Q.773 for that Component type.
	Length indicator value less than 128 octets, but not coded short form.

**3.7.2.8 unexpected linked operation:** The operation referred to by the linked ID does not allow this linked operation. This code is generated only by the TC-User.

**3.7.3 return result problem:** This element contains one of the problem codes which relate only to the return result component type. They are:

**3.7.3.1 unrecognized invoke ID:** No operation with the specified invoke ID is in progress. This code is generated by the component sublayer.

**3.7.3.2 return result unexpected:** The invoked operation does not report success. This code is generated by the component sublayer.

**3.7.3.3 mistyped parameter:** Signifies that the type of parameter in the return result component is not that agreed by the two TC-Users.

**3.7.4 return error problem:** This element contains one of the problem codes that relate only to the return error component type. They are:

**3.7.4.1 unrecognized invoke ID:** No operation with the specified invoke ID is in progress. This code is generated by the component sublayer.

**3.7.4.2 return error unexpected:** The invoked operation does not report failure. This code is generated by the component sublayer.

**3.7.4.3 unrecognized error:** The error code is not one of those agreed by the two TC-User.

**3.7.4.4 unexpected error:** The received error is not one of those that the invoked operation may report. This code is generated by the TC-User.

**3.7.4.5 mistyped parameter:** Signifies that the type parameter in a Return Error component is not that agreed by the two TC-Users.

## 4 Dialogue portion

The dialogue portion contains a dialogue control Application Protocol Data Unit (APDU) or user information.

### 4.1 Dialogue control APDUs

Each dialogue control APDU defined is compatible with the OSI ACSE APDUs defined in Recommendation X.227.

The mapping between Dialogue Control APDUs and those of the OSI ACSE are shown below.

Dialogue Control APDU	ACSE APDU
Dialogue Request	AARQ
Dialogue Response	AARE
Dialogue Abort	ABRT
Dialogue Uni	AUDT

**4.1.1 Dialogue Request (AARQ) APDU:** The Dialogue Request (AARQ) APDU is used by the initiating TC-User at the start of a transaction to convey the Application Context Name and, as an option, user information (i.e. data, which are not components) to the peer TC-User.

**4.1.2 Dialogue Response (AARE) APDU:** The Dialogue Response (AARE) APDU is used by the responding TC-User in the first backward message to inform the originating TC-User on whether or not the dialogue is accepted.

**4.1.3 Dialogue Abort (ABRT) APDU:** The Dialogue Abort (ABRT) APDU is used by the component sublayer to inform its peer of the receipt of an abnormal (syntactically invalid or inopportune) dialogue portion APDU. It is also used by the TC-Users to terminate a dialogue due to an abnormal situation.

**4.1.4 Dialogue Uni (AUDT) APDU:** The Dialogue Uni (AUDT) APDU is used to convey the Application Context Name and, as an option, user information (i.e. data, which are not components) for the situation where there is no need to establish a dialogue between two TC-Users.

### 4.2 Dialogue portion information elements

**4.2.1 application context name:** This parameter, of the form OBJECT IDENTIFIER, is a reference to an explicitly defined set of the TC-User Application Service Elements (ASEs), related options and any other necessary information for the interworking of two TC-Users during an instance of communication.

**4.2.2 protocol version:** The protocol version information element indicates the versions of the Dialogue Portion that can be supported. It is a bit string, where each bit that is set to one indicates the version of the dialogue portion that is supported. Bit 0 represents version 1, bit 1 represents version 2, etc. The last bit set to one in the bit string is the highest selected version. When the

Protocol version parameter is absent, it implies "version 1" which is the version corresponding to this Recommendation.

**4.2.3 user information:** User information corresponds to any information exchanged between two TC-Users. Its meaning depends on the Application Context Name that accompanies it or is in place during its use. For example, this parameter may be used to carry information that further refines the application context by providing the "versions" of the ASEs that are referenced, "initialization" information on the ASEs, etc. Its meaning and use are therefore outside the scope of these Recommendations.

**4.2.4 result:** This parameter is set by the component sublayer to provide the initiating TC-User with the result of the request to establish a dialogue. Its value is set based on the dialogue handling primitive (and its accompanying parameters) used by the responding TC-User in response to the request for a dialogue. It takes the values "accepted" or "rejected (permanent)". The use of the value "rejected (transient)" is for further study.

**4.2.5 result source diagnostic:** This parameter identifies the creating source of the Result parameter and qualifies the result with some diagnostic information. The value of this parameter is set by the component sublayer and takes the symbolic values "dialogue service user" or "dialogue service provider". If the Result parameter takes the value "accepted", this parameter's value is set to "dialogue service user".

The "dialogue service user" can further qualify the result with a diagnostic with values of "null" or "no reason given" (for the case where no diagnostic is offered) or "application-context-name-not-supported" for the case when the dialogue is refused because the application context is not supported. The "dialogue service provider" can further qualify the result with a diagnostic with values of "null" or "no reason given" (for the case where no diagnostic is offered) or "no common-dialogue-portion" (for the case, supporting the future evolution of these Recommendations, when the dialogue portions of the peer TC are different).

**4.2.6 abort source:** This parameter identifies whether the abnormal release of the dialogue is due to a request by the TC-User or the initiated by the dialogue portion for which it takes the values, respectively, of "dialogue service user" or "dialogue service provider".

## ITU-T RECOMMENDATIONS SERIES

- Series A Organization of the work of the ITU-T
- Series B Means of expression: definitions, symbols, classification
- Series C General telecommunication statistics
- Series D General tariff principles
- Series E Overall network operation, telephone service, service operation and human factors
- Series F Non-telephone telecommunication services
- Series G Transmission systems and media, digital systems and networks
- Series H Audiovisual and multimedia systems
- Series I Integrated services digital network
- Series J Transmission of television, sound programme and other multimedia signals
- Series K Protection against interference
- Series L Construction, installation and protection of cables and other elements of outside plant
- Series M TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
- Series N Maintenance: international sound programme and television transmission circuits
- Series O Specifications of measuring equipment
- Series P Telephone transmission quality, telephone installations, local line networks
- Series Q Switching and signalling**
- Series R Telegraph transmission
- Series S Telegraph services terminal equipment
- Series T Terminals for telematic services
- Series U Telegraph switching
- Series V Data communication over the telephone network
- Series X Data networks and open system communication
- Series Z Programming languages